

# Polycom Phone Installation Guide

FEBRUARY 2021

Release 1

2925-001



## **NOTICE**

The information contained in this document is believed to be accurate in all respects but is not warranted by Clearspan LLC (Clearspan®). The information is subject to change without notice and should not be construed in any way as a commitment by Clearspan or any of its affiliates or subsidiaries. Clearspan and its affiliates and subsidiaries assume no responsibility for any errors or omissions in this document. Revisions of this document or new editions of it may be issued to incorporate such changes.

No part of this document can be reproduced or transmitted in any form or by any means - electronic or mechanical - for any purpose without written permission from Clearspan LLC.

## **TRADEMARKS**

The trademarks, service marks, logos and graphics (collectively "Trademarks") appearing on Clearspan's Internet sites or in its publications are registered and unregistered trademarks of Clearspan LLC. Use of the Trademarks is prohibited without the express consent from Clearspan.

Polycom Phone Installation Guide  
Release #1 February 2021

®,™ Trademark of Clearspan LLC  
© Copyright 2021 Clearspan LLC  
All rights reserved

Contents

REVISION HISTORY..... 1

OVERVIEW..... 2

INSTALLATION ..... 3

ADDITIONAL PROCEDURES ..... 8

    Restarting Phones..... 8

    Factory default phones ..... 10

# REVISION HISTORY

---

The following represents the revision history of this publication:

REVISION	DATE COMPLETED	POINT OF CONTACT	AFFECTED SECTIONS
1	02/2021	Clearspan Technical Publications	All

## OVERVIEW

---

This document shows the steps to bring up a Polycom VVX Series Phone after the Phone Type is configured in Clearspan and the User and Device is configured in OpEasy.

# INSTALLATION

The following table lists the Polycom Phone Installation Steps and the expected results:

	<b>ACTION</b>	<b>EXPECTED RESULTS</b>
<b>Create Users and Devices</b>		
1	Create a User and Assign the User a Polycom VVX Phone with OpEasy	
2	Starting with a Factory Defaulted Phone	
<b>Determine IP Address of the VVX 300, 301, 310 &amp; 311 Phones</b>		
3	Press the <b>Home</b> button 	The <b>Options</b> list is displayed
4	Using the <b>Navigation/Select</b> Keys  Scroll to <b>Settings</b>  Press the <b>Select</b> button	The <b>Settings</b> menu is displayed
5	Scroll to Status Press <b>Select</b>	The <b>Status</b> menu is displayed
6	Scroll to Network Press <b>Select</b>	The <b>Network</b> menu is displayed
7	Select TCP/IP Parameters Press <b>Select</b>	The <b>TCP/IP Parameters</b> page is displayed The <b>IP Address</b> is displayed
<b>Determine IP Address of the VVX 400, 401, 410 &amp; 411 Phones</b>		
8	Press the <b>Home</b> button 	The <b>Options</b> page is displayed
9	Select <b>Settings</b>	The <b>Settings</b> menu is displayed

	 <p>Press the <b>Select</b> button</p>	
10	<p>Scroll to Status</p> <p>Press <b>Select</b></p>	The <b>Status</b> menu is displayed
11	<p>Scroll to Network</p> <p>Press <b>Select</b></p>	The <b>Network</b> menu is displayed
12	<p>Select TCP/IP Parameters</p> <p>Press <b>Select</b></p>	The <b>TCP/IP Parameters</b> page is displayed The <b>IP Address</b> is displayed
<p><b>Determine IP Address of the VVX 500, 501, 600 &amp; 601 Phones</b></p>		
13	<p>Press the <b>Home</b> button</p> 	The <b>Settings</b> screen is displayed
14	<p>Touch <b>Settings</b></p> 	The <b>Settings</b> menu is displayed
15	<p>Touch <b>Status</b></p>	The <b>Status</b> menu is displayed
16	<p>Touch <b>Network</b></p>	The <b>Network</b> menu is displayed
17	<p>Touch <b>TCP/IP Parameters</b></p>	The <b>TCP/IP Parameters</b> page is displayed The <b>IP Address</b> is displayed
<p><b>Phone Configuration if DHCP Server Address is Available</b></p>		
18	<p>The Factory Defaulted Phone will display on the Phone's screen the Unregistered Phone Symbol</p>  <p>Or</p> 	The Soft Key line will display <b>QSetup</b>
19	<p>Press the <b>QSetup</b> button</p>	The Quick Setup page is displayed.

20	Select the Server User row Press the <b>Edit</b> button or touch the row	The Server User row is enabled
21	Enter the OpEasy Device Access User Name, PlcmSplp is overwritten Press/Touch <b>OK</b>	The <b>Server User/OpEasy Device Access User</b> is displayed in Cleartext
22	Scroll to Server Password row Press the <b>Edit</b> button or touch the row	The Server Password row is enabled
23	Enter the OpEasy Device Access Password The password will display the character and then ● Press/Touch <b>OK</b>	The <b>Server User/OpEasy Device Access User</b> is displayed as ●●●●
24	Press <b>Exit</b> or ←	The phone's screen will display: Exit w/o Save Save Config Resume Setup Save Config is hi-lighted
25	Select <b>Save Config</b> or touch the row	The Phone will reboot After a few restarts the phone's correct configuration will display
<b>Phone Configuration if DHCP Server Address is not Available</b>		
26	Log into the Phone's web portal ie. http://<Phone's IP> or https://<Phone's IP>	The <b>Welcome to Polycom Web Configuration Utility</b> box is displayed
27	Select the <b>Admin radio</b> button Enter Password: 456 Click <b>Submit</b>	The <b>Polycom Home</b> page is displayed
28	Select <b>Setting</b> → Provisioning Server	The <b>Provisioning Server</b> page is displayed
29	Select HTTPS from the <b>Server Type</b> drop-down list Enter the Server Address ie. https://tb20xsp.cslab.mitel.com:443/clearspan Enter the OpEasy Device Access User Name in the Server User box, overwrite PlcmSplp  Enter the OpEasy Device Access Password in the Server Password box, overwrite ●●●●  Click <b>Save</b>	A <b>Confirmation</b> box is displayed

30	Click <b>Yes</b>	The Phone will restart After a few restarts the phone's correct configuration will display
<b>When Admin Cannot Log into the Web Portal</b>		
31	Press the <b>Home</b> button 	The <b>Options</b> list is displayed
32	Using the Navigation/Select Keys  Scroll to Settings  Press the <b>Select</b> button	The <b>Settings</b> menu is displayed
33	Scroll to Advanced Press <b>Select</b>	<b>Password page</b> is displayed
34	Enter the Default Password, 456 Press <b>Enter</b>	The <b>Advanced menu</b> is displayed
35	Select <b>Administration Settings</b> Press <b>Select</b>	The <b>Administration Setting</b> menu is displayed
36	Select <b>Network Configuration</b> Press <b>Select</b>	The <b>Network Configuration</b> menu is displayed
37	Select <b>Provisioning Server</b> Press <b>Select</b>	The <b>Provisioning Server</b> menu is displayed
38	Scroll to Server Type Press <b>Edit</b>	The <b>Server Type</b> list is displayed
39	Scroll to HTTPS Press <b>Select</b>	The <b>Provisioning Server</b> menu is displayed
40	Scroll to Server Address Press <b>Edit</b>	The Server Address box is Enabled
41	Enter the complete Provisioning Server Address ie. <a href="https://tb20xsp.cslab.mitel.com:443/dms/clearspan">https://tb20xsp.cslab.mitel.com:443/dms/clearspan</a> Press <b>OK</b>	The Server Address box is Disabled
42	Scroll to Server User	The Server User box is Enabled

	Press <b>Edit</b>	
43	Enter the OpEasy Device Access User Name, overwrite PlcmSplp Press <b>OK</b>	The Server User box is Disabled The Server User/OpEasy Device Access User is displayed in Cleartext
44	Scroll to Server Password Press <b>Edit</b>	The <b>Server Password</b> box is Enabled
45	Enter the OpEasy Device Access Password, overwrite the symbols. The password will display the character and then • Press <b>OK</b>	The <b>Server User/OpEasy Device Access User</b> is displayed as ****
46	Press <b>Back</b>	The <b>Network Configuration</b> menu is displayed
47	Press <b>Back</b>	Exit w/o Save Save Config Resume Setup Is displayed on the phone's screen Save Config is hi-lighted
48	Select <b>Save Config</b> Press <b>Select</b>	The Phone will reboot After a few restarts the phone's correct configuration will display

## ADDITIONAL PROCEDURES

The following section lists the additional procedures for restarting a phone.

### RESTARTING PHONES

	ACTION	EXPECTED RESULTS
<b>Restart VVX 300, 301, 310 &amp; 311</b>		
1	Press the <b>Home</b> button 	The <b>Options</b> list is displayed
2	Using the <b>Navigation/Select</b> Key  Scroll to the <b>Settings</b> icon  Press the <b>Select</b> button	The <b>Settings</b> menu is displayed
3	Scroll to <b>Advanced</b> Press <b>Select</b>	The <b>Password</b> page is displayed
4	Enter the Admin Password Press <b>Enter</b>	The <b>Advanced</b> menu is displayed
5	Scroll to <b>Reboot Phone</b> Press <b>Select</b>	The <b>Reboot Phone</b> page is displayed with the question Are you sure?
6	Press <b>Yes</b>	The Phone will reboot
<b>Restart VVX 400, 401, 410 &amp; 411</b>		
7	Press the <b>Home</b> button 	The <b>Options</b> list is displayed
8	Use the <b>Navigation/Select</b> Key  to hi-light the <b>Settings</b> icon  Press the <b>Select</b> button	The <b>Settings</b> menu is displayed
9	Scroll to <b>Advanced</b>	The <b>Password</b> page is displayed

	Press <b>Select</b>	
10	Enter the Admin Password Press <b>Enter</b>	The <b>Advanced</b> menu is displayed
11	Scroll to Reboot Phone Press <b>Select</b>	The Reboot Phone page is displayed with the question Are you sure?
12	Press <b>Yes</b>	The Phone will reboot
<b>Restart VVX 500, 501, 600 &amp; 601</b>		
13	Press the <b>Home</b> button 	The <b>Options</b> list is displayed
14	Touch the <b>Settings</b> icon 	The <b>Settings</b> menu is displayed
15	Touch <b>Advanced</b>	The <b>Password</b> page is displayed
16	Enter the Admin Password Touch <b>Enter</b>	The <b>Advanced</b> menu is displayed
17	Touch <b>Reboot Phone</b>	The Reboot Phone page is displayed with the question Are you sure?
18	Touch <b>Yes</b>	The Phone will reboot

## FACTORY DEFAULT PHONES

<b>Factory Default VVX 300, 301, 310 &amp; 311</b>		
1.	<p>Press the <b>Home</b> button</p> 	The <b>Options</b> list is displayed
2.	<p>Using the <b>Navigation/Select</b> Key</p>  <p>Scroll to the Settings icon</p>  <p>Press the <b>Select</b> button</p>	The <b>Settings</b> menu is displayed
3.	<p>Scroll to Advanced</p> <p>Press <b>Select</b></p>	The <b>Password</b> page is displayed
4.	<p>Enter the Phones Admin Password</p> <p>Press <b>Enter</b></p>	The <b>Advanced</b> menu is displayed
5.	<p>Select <b>Administration Settings</b></p> <p>Press <b>Select</b></p>	The <b>Administration Settings</b> menu is displayed
6.	<p>Scroll to Reset to Defaults</p> <p>Press <b>Select</b></p>	The <b>Reset to Defaults</b> menu is displayed
7.	<p>Scroll to Reset to Factory</p> <p>Press <b>Select</b></p>	The Reset to Factory page is displayed with the question Are you sure?
8.	<p>Press <b>Yes</b></p>	The Phone will reboot
<b>Factory Default VVX 400, 401, 410 &amp; 411</b>		
9.	<p>Press the <b>Home</b> button</p> 	The <b>Options</b> list is displayed
10.	<p>Use the <b>Navigation/Select</b> Key</p>  <p>to hi-light the Settings icon</p>	The <b>Settings</b> menu is displayed

	 <p>Press the <b>Select</b> button</p>	
11.	<p>Scroll to <b>Advanced</b> Press <b>Select</b></p>	The <b>Password</b> page is displayed
12.	<p>Enter the Phones Admin Password Press <b>Enter</b></p>	The <b>Advanced</b> menu is displayed
13.	<p>Select <b>Administration Settings</b> Press <b>Select</b></p>	The <b>Administration Settings</b> menu is displayed
14.	<p>Scroll to <b>Reset to Defaults</b> Press <b>Select</b></p>	The <b>Reset to Defaults</b> menu is displayed
15.	<p>Scroll to <b>Reset to Factory</b> Press <b>Select</b></p>	The <b>Reset To Factory</b> page is displayed with the question Are you sure?
16.	<p>Press <b>Yes</b></p>	The Phone will reboot
<p><b>Factory Default VVX 500, 501, 600 &amp; 601</b></p>		
17.	<p>Press the <b>Home</b> button</p> 	The <b>Options</b> list is displayed
18.	<p>Touch the <b>Settings</b> icon</p> 	The <b>Settings</b> menu is displayed
19.	<p>Touch <b>Advanced</b></p>	The <b>Password</b> page is displayed
20.	<p>Enter the Phones Admin Password Touch <b>Enter</b></p>	The <b>Advanced</b> menu is displayed
21.	<p>Touch <b>Administration Settings</b></p>	The <b>Administration Settings</b> menu is displayed
22.	<p>Touch <b>Reset to Defaults</b></p>	The <b>Reset to Defaults</b> menu is displayed
23.	<p>Touch <b>Reset to Factory</b></p>	The <b>Reset To Factory page</b> is displayed with the question Are you sure?
24.	<p>Touch <b>Yes</b></p>	The Phone will reboot

This document contains sensitive and proprietary information and company trade secrets that are critical to Clearspan business. This information may not be disclosed to any person or party without the express written consent of Clearspan. This document may not be reproduced in full or in part without the express permission of an officer or director of Clearspan.